

Check Reader/ HCR-2000



HANTLE SYSTEM

Features

- MICR font (E13B or CMC7) recognition
- Multiple algorithms for higher read rate
- Various interface with RS-232, RS-485, keyboard wedge, TTL
- Compact size and stylish design
- Bundle check feeding mechanism (up to 50 checks)
- Two LED indicators (good / error)
- Optional built-in inkjet printer for 1 line endorsement

Check Reader / HCR-2000

Check Reader / HCR -2000

Applications

Check deposit or issue logging in banking terminal
Fraud check black list search in CAT terminal
Personal check balance inquiry in POS terminal
General MICR reader

Specifications

General

MICR font standard	E13B, CMC7
Feed speed	300mm/sec
Read speed	60sheets/min
E13B read rate	99.5%
CMC7 read rate	99.9%
Inkjet printer	12pin inkjet, ASCII characters

Lifetime

Magnetic head	600,000 passes
---------------	----------------

Interface

Communication	RS-232C, RS-485, PC KEYBOARD, TTL
AC/DC adapter	AC 110V/220V input, DC 12V/800mA output

Physical

Size	102mm(W)X 96mm(H)X 204mm(L)(without guide)
Weight	1320g(without adapter)

Environmental

Operating temperature	5°C ~ 40°C
Operating humidity	10 ~ 80% RH, non condensing
Storage temperature	-20°C ~ 60°C
Storage humidity	0 ~ 90% RH, non condensing

HANTLE SYSTEM

Byucksan/kyungin digital Valley II 1511, 481-10,
Kasan-dong, Kumchon-gu, Seoul, Korea
Tel : 82 2 3282 2500 (Rep.) 2570/6 (Sales Div.) Fax : 82 2 853 8787
Web site : <http://www.hantle.com>

After this June, 2000-based catalogue, items could changed or added according to our situation.